

## Cata-Dyne™ Heating Technology

The Cata-Dyne™ WX Series explosion-proof heater is a revolutionary product with uniform heat distribution, high fuel efficiencies, more radiant power and a certified explosion-proof rating. It is 33% more fuel efficient than older models producing the same energy output.

Most Cata-Dyne™ heaters for oil and gas applications are started with either 12V or 120V electrical elements (24, 208, 240 and 600V are also available,) but power is only required during the initial startup. No power is needed to operate the heaters or their controls once the heater has started and the catalytic reaction has been established.

## Introducing the Cata-Dyne™ Slim Line..

Since its introduction in 1965 the Cata-Dyne™ heater has established itself as the benchmark in explosion-proof infrared heating. Over the years we've made several refinements to these first rate heaters and now, with the introduction of the Cata-Dyne™ Slim Line we've raised the bar again offering heaters ideal for enclosures and tight spaces.

### 1½ in. Thinner Design for Space Installation Constraints

All Slim Line heaters are equipped with universal mounting brackets and can easily be mounted into existing facilities or enclosures.



### Approved Ratings for Your Application

The Slim Line carries FM, Class I, Div 1, Group D explosion-proof ratings.

#### Cata-Dyne™ Heater Selection



3 in. Insulation for Optimal Radiant Power



Side Mounted Operating Controls for Easy Access



1½ in. Thinner Design for Space Installation Constraints